

View Online at <https://aerobasegroup.com/nsn/6625-00-237-8751>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

2000.0

**Reliability Indicator:**

Not established

**Overall Length:**

1.350 inches

**Overall Height:**

3.250 inches

**Overall Width:**

3.250 inches

**Mounting Hole Diameter:**

0.125 inches

**Scale Division Quantity:**

30 single indicator single range

**Environmental Protection:**

Dust resistant

**Mounting Bolt Circle Diameter:**

2.240 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud bolt circle

**Frequency Response Range:**

+0.000/+400.000 hertz

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.080 inches

**Meter Body Diameter Behind Mounting Flange:**

2.730 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0/+3.0 amperes, ac single indicator single range

**Scale Selection Method:**

Terminal

**Features Provided:**

Zero adjuster

**Circuit Attachment Method And Quantity:**

2 solder stud

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0