

View Online at <https://aerobasegroup.com/nsn/6625-00-237-8904>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

2.740 inches

**Mounting Hole Diameter:**

0.147 inches

**Overall Diameter:**

3.500 inches

**Mounting Bolt Circle Diameter:**

3.160 inches

**Indicator Type:**

Vibrating reed

**Installation Design:**

Panel

**Register Quantity:**

1

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Frequency Response Range:**

+55.000 to 65.000 hertz

**Resonant Reed Quantity:**

11

**Meter Depth Behind Mounting Flange:**

1.930 inches

**Meter Body Diameter Behind Mounting Flange:**

2.780 inches

**Movement Type:**

Vibrating reed

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Measurement Range:**

+55.0 to 65.0 hertz single indicator single range

**Circuit Attachment Method And Quantity:**

2 solder lug and 2 threaded stud

**Operating Voltage Rating In Volts:**

Between 100.0 ac and 150.0 ac

**Special Features:**

Porm 0.3 pct accuracy of calibration

**Material:**

Plastic phenol-formaldehyde

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0