

View Online at <https://aerobasegroup.com/nsn/6625-00-237-8904>

Circuit Current For Which Designed:

Ac

Overall Length:

2.740 inches

Mounting Hole Diameter:

0.147 inches

Overall Diameter:

3.500 inches

Mounting Bolt Circle Diameter:

3.160 inches

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+55.000 to 65.000 hertz

Resonant Reed Quantity:

11

Meter Depth Behind Mounting Flange:

1.930 inches

Meter Body Diameter Behind Mounting Flange:

2.780 inches

Movement Type:

Vibrating reed

Mounting Facility Type And Quantity:

3 unthreaded hole

Measurement Range:

+55.0 to 65.0 hertz single indicator single range

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Operating Voltage Rating In Volts:

Between 100.0 ac and 150.0 ac

Special Features:

Porm 0.3 pct accuracy of calibration

Material:

Plastic phenol-formaldehyde

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0