## NSN 6625-00-237-9326

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-237-9326

| Circuit Current For Which Designed:                   |
|---|
| Ac  |
| Dielectric Withstanding Voltage In Volts:             |
| 2000.0  |
| Overall Length:                                       |
| 1.785 inches  |
| Mounting Hole Diameter:                               |
| 0.125 inches  |
| Scale Division Quantity:                              |
| 25 single indicator single range                      |
| Overall Diameter:                                     |
| 3.500 inches  |
| Environmental Protection:                             |
| Dust resistant  |
| Mounting Bolt Circle Diameter:                        |
| 1.580 inches  |
| Indicator Type:                                       |
| Dial w/pointer  |
| Installation Design:                                  |
| Panel   |
| Mounting Arrangement Style:                           |
| Three hole/stud bolt circle                           |
| Sensitivity Rating:                                   |
| 45.0 millivolts                                       |
| Dial Scale Marking Color:                             |
| Black single indicator single range                   |
| Accuracy In Percent:                                  |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange:                   |
| 1.660 inches  |
| Meter Body Diameter Behind Mounting Flange:           |
| 2.800 inches  |
| Movement Type:  |
| Moving iron vane                                      |
| Background Color:                                     |
| White single indicator single range                   |
| Pointer Color:  |
| Black single indicator single range                   |
| Power Source:   |
| External  |
| Mounting Facility Type And Quantity:                  |
|   |

3 unthreaded hole

## NSN 6625-00-237-9326

Ammeter - Page 2 of 2



| Scale Graduation Type:                                     |
|--|
| Linear single indicator single range                       |
| Measurement Range:   |
| +0.0/+250.0 milliamperes, ac single indicator single range |
| Scale Selection Method:                                    |
| Terminal   |
| Movement Suspension Method:                                |
| Taut band  |
| Circuit Attachment Method And Quantity:                    |
| 2 solder stud  |
| Material:  |
| Plastic  |
| Nuclear Hardness Critical Feature:                         |
| Nonhardened  |
| Style Designator:  |
| Round flush mtg  |
| Shelf Life:  |
| Shelf Life:  |
| N/a  |
|  |
| N/a  |
| N/a<br>Unit Of Measure:                                    |
| N/a<br>Unit Of Measure:<br>                                |
| N/a<br>Unit Of Measure:<br><br>Demilitarization:           |
| N/a<br>Unit Of Measure:<br><br>Demilitarization:<br>No     |