

View Online at <https://aerobasegroup.com/nsn/6625-00-239-7405>

Mounting Hole Diameter:

0.125 inches

Overall Diameter:

3.250 inches

Mounting Bolt Circle Diameter:

1.438 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+59.000 to 61.000 hertz

Resonant Reed Quantity:

5

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.562 inches

Meter Body Diameter Behind Mounting Flange:

2.344 inches

Movement Type:

Vibrating reed

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Measurement Range:

+59.0 to 61.0 hertz single indicator single range

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Tropicalized

Special Markings:

3600 rpm slow fast above scale; motor speed below scale

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0