

View Online at <https://aerobasegroup.com/nsn/6625-00-242-5502>

Circuit Current For Which Designed:

Ac

Overall Length:

4.750 inches

Overall Height:

3.000 inches

Overall Width:

1.250 inches

Mounting Hole Diameter:

0.238 inches

Scale Division Quantity:

20 single indicator single range

Frequency Rating:

60.0 hertz

Distance Between Mounting Facility Centers:

0.750 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

0.1 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

4.000 inches

Meter Body Diameter Behind Mounting Flange:

1.138 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Extended center and end marks; 21 graduation marks

Mounting Facility Type And Quantity:

2 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Unit shall include self contained magnet

Material:

Aluminum

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Supplementary Features:

External damping res 1000 ohms porm 20 pct

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0