

View Online at <https://aerobasegroup.com/nsn/6625-00-242-5502>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

4.750 inches

**Overall Height:**

3.000 inches

**Overall Width:**

1.250 inches

**Mounting Hole Diameter:**

0.238 inches

**Scale Division Quantity:**

20 single indicator single range

**Frequency Rating:**

60.0 hertz

**Distance Between Mounting Facility Centers:**

0.750 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Two hole/stud

**Sensitivity Rating:**

0.1 microamperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

4.000 inches

**Meter Body Diameter Behind Mounting Flange:**

1.138 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

Extended center and end marks; 21 graduation marks

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 solder lug

**Special Features:**

Unit shall include self contained magnet

**Material:**

Aluminum

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Supplementary Features:**

External damping res 1000 ohms porm 20 pct

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0