NSN 6625-00-242-6888

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-242-6888

view Online at https://aerobasegroup.com/nsn/6625-00-242-6666
Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.650 inches
Mounting Hole Diameter:
Between 0.120 inches and 0.130 inches
Scale Division Quantity:
6 single indicator 1st range
Overall Diameter:
2.695 inches
Environmental Protection:
Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight
Mounting Bolt Circle Diameter:
2.440 inches
Furnished Items And Quantity:
Nut 3; lockwasher 3
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
100.0 microamperes
Dial Scale Marking Color:
Black single indicator 2nd range and green single indicator 2nd range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator all ranges
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.875 inches
Meter Body Diameter Behind Mounting Flange:
2.210 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator all ranges

Pointer Color:

Black single indicator all ranges

NSN 6625-00-242-6888

Special Scale Meter - Page 2 of 2

Fiig: A310a0



Scale Marking:
Top scale: kmc; 16.2; 16.3; 16.4; 16.5; 16.6; 16.7; 16.8; 2nd scale: power; green band at 48 ua to 52 ua deflection; 3rd scale: pct
dither; 0; 50; 100; 150; 200
Mounting Facility Type And Quantity:
3 screw and 3 unthreaded hole
Scale Graduation Type:
Linear single indicator all ranges
Features Provided:
Magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug
Special Features:
Ruggedized
Special Markings:
Top scalemarked kmc, middle scale marked power, green area at center scale, bottom scale marked dither
Material:
Stainless steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel semigloss
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No