

View Online at <https://aerobasegroup.com/nsn/6625-00-243-6635>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Overall Length:**

1.625 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 1.306 inches and 1.318 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

Between 1.306 inches and 1.318 inches

**Overall Height:**

Between 1.734 inches and 1.766 inches

**Overall Width:**

Between 1.734 inches and 1.766 inches

**Mounting Stud Length:**

Between 0.313 inches and 0.437 inches

**Furnished Items And Quantity:**

Nuts 4, washers 4

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-3.0 to 3.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.000 inches

**Meter Body Diameter Behind Mounting Flange:**

1.510 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Mounting Facility Type And Quantity:**

4 threaded stud

**Mounting Stud Diameter:**

Between 0.120 inches and 0.130 inches

**Features Provided:**

Magnetic shield

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder lug

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0