

View Online at <https://aerobasegroup.com/nsn/6625-00-246-5016>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

2500.0

Overall Length:

1.719 inches

Overall Height:

1.906 inches

Overall Width:

2.000 inches

Scale Division Quantity:

4 single indicator single range

Mounting Stud Length:

0.781 inches

Distance Between Mounting Facility Centers:

0.969 inches

Furnished Items And Quantity:

Nut 2; washer 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Movement Type:

Moving iron vane

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Scale Marking:

D; c; alt

Mounting Facility Type And Quantity:

2 threaded stud

Scale Graduation Type:

Linear single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Circuit attachment and mounting method use same 2 threaded studs

Material:

Aluminum

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0