## NSN 6625-00-248-7208

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-248-7208

Overall Length: 1.410 inches Mounting Hole Diameter: 0.156 inches Scale Division Quantity: 40 single indicator single range Overall Diameter: 3.510 inches Mounting Bolt Circle Diameter: 3.160 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range Features Provided:				
Mounting Hole Diameter:  0.156 inches  Scale Division Quantity: 40 single indicator single range  Overall Diameter: 3.510 inches  Mounting Bolt Circle Diameter: 3.160 inches  Installation Design: Panel  Mounting Arrangement Style: Three hole/stud bolt circle  Sensitivity Rating: 11.0 millivolts  Dial Scale Marking Color: Black single indicator single range  Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 1.030 inches  Meter Body Diameter Behind Mounting Flange: 2.760 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator single range  Measurement Range: +0.0/+20.0 microamperes, dc single indicator single range				
Mounting Hole Diameter:  0.156 inches  Scale Division Quantity:  40 single indicator single range  Overall Diameter:  3.510 inches  Mounting Bolt Circle Diameter:  3.160 inches  Installation Design: Panel  Mounting Arrangement Style: Three hole/stud bolt circle  Sensitivity Rating:  11.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:  -2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  1.030 inches  Meter Body Diameter Behind Mounting Flange:  2.760 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator single range  Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range				
O.156 inches  Scale Division Quantity:  40 single indicator single range  Overall Diameter:  3.510 inches  Mounting Bolt Circle Diameter:  3.160 inches  Installation Design:  Panel  Mounting Arrangement Style:  Three hole/stud bolt circle  Sensitivity Rating:  11.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:  -2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  1.030 inches  Meter Body Diameter Behind Mounting Flange:  2.760 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator single range  Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range				
Scale Division Quantity: 40 single indicator single range Overall Diameter: 3.510 inches Mounting Bolt Circle Diameter: 3.160 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range				
Overall Diameter: 3.510 inches Mounting Bolt Circle Diameter: 3.160 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range				
Overall Diameter: 3.510 inches Mounting Bolt Circle Diameter: 3.160 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range				
3.510 inches  Mounting Bolt Circle Diameter: 3.160 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range				
Mounting Bolt Circle Diameter: 3.160 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range				
Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range				
Installation Design: Panel  Mounting Arrangement Style: Three hole/stud bolt circle  Sensitivity Rating: 11.0 millivolts  Dial Scale Marking Color: Black single indicator single range  Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 1.030 inches  Meter Body Diameter Behind Mounting Flange: 2.760 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator single range  Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range				
Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range				
Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range				
Three hole/stud bolt circle  Sensitivity Rating:  11.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:  -2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  1.030 inches  Meter Body Diameter Behind Mounting Flange:  2.760 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator single range  Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range				
Sensitivity Rating:  11.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:  -2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  1.030 inches  Meter Body Diameter Behind Mounting Flange:  2.760 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator single range  Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range				
11.0 millivolts  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:  -2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  1.030 inches  Meter Body Diameter Behind Mounting Flange:  2.760 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator single range  Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range				
Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:  -2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  1.030 inches  Meter Body Diameter Behind Mounting Flange:  2.760 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator single range  Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range				
Black single indicator single range  Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 1.030 inches  Meter Body Diameter Behind Mounting Flange: 2.760 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator single range  Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range				
Accuracy In Percent:  -2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  1.030 inches  Meter Body Diameter Behind Mounting Flange:  2.760 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator single range  Measurement Range:  +0.0/+200.0 microamperes, dc single indicator single range				
-2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  1.030 inches  Meter Body Diameter Behind Mounting Flange:  2.760 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator single range  Measurement Range:  +0.0/+200.0 microamperes, dc single indicator single range				
Meter Depth Behind Mounting Flange:  1.030 inches  Meter Body Diameter Behind Mounting Flange:  2.760 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator single range  Measurement Range:  +0.0/+200.0 microamperes, dc single indicator single range				
1.030 inches  Meter Body Diameter Behind Mounting Flange: 2.760 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator single range  Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range				
Meter Body Diameter Behind Mounting Flange: 2.760 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator single range  Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range				
2.760 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator single range  Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range				
Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator single range  Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range				
Moving coil, permanent magnet  Background Color:  White single indicator single range  Measurement Range:  +0.0/+200.0 microamperes, dc single indicator single range				
Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range				
White single indicator single range  Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range				
Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range				
+0.0/+200.0 microamperes, dc single indicator single range				
Features Provided:				
Magnetic shield				
Movement Suspension Method:				
Jewel pivot base				
Circuit Attachment Method And Quantity:				
2 threaded stud				
Material:				
Plastic				

Round flush mtg

## NSN 6625-00-248-7208

Ammeter - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A310a0