NSN 6625-00-248-7208

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-248-7208

Overall Length: 1.410 inches Mounting Hole Diameter: 0.156 inches Scale Division Quantity: 40 single indicator single range Overall Diameter: 3.510 inches Mounting Bolt Circle Diameter: 3.160 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range Features Provided:
Mounting Hole Diameter: 0.156 inches Scale Division Quantity: 40 single indicator single range Overall Diameter: 3.510 inches Mounting Bolt Circle Diameter: 3.160 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+20.0 microamperes, dc single indicator single range
Mounting Hole Diameter: 0.156 inches Scale Division Quantity: 40 single indicator single range Overall Diameter: 3.510 inches Mounting Bolt Circle Diameter: 3.160 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
O.156 inches Scale Division Quantity: 40 single indicator single range Overall Diameter: 3.510 inches Mounting Bolt Circle Diameter: 3.160 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
Scale Division Quantity: 40 single indicator single range Overall Diameter: 3.510 inches Mounting Bolt Circle Diameter: 3.160 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
Overall Diameter: 3.510 inches Mounting Bolt Circle Diameter: 3.160 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
Overall Diameter: 3.510 inches Mounting Bolt Circle Diameter: 3.160 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
3.510 inches Mounting Bolt Circle Diameter: 3.160 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
Mounting Bolt Circle Diameter: 3.160 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
Mounting Arrangement Style: Three hole/stud bolt circle Sensitivity Rating: 11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
Three hole/stud bolt circle Sensitivity Rating: 11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
Sensitivity Rating: 11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
11.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
-2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
Meter Depth Behind Mounting Flange: 1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
1.030 inches Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
Meter Body Diameter Behind Mounting Flange: 2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
2.760 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
Moving coil, permanent magnet Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
Background Color: White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
White single indicator single range Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
Measurement Range: +0.0/+200.0 microamperes, dc single indicator single range
+0.0/+200.0 microamperes, dc single indicator single range
Features Provided:
Magnetic shield
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Material:
Plastic

Round flush mtg

NSN 6625-00-248-7208

Ammeter - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0