NSN 6625-00-250-7021

Arbitrary Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-250-7021

| Circuit Current For Which Designed: | | | | |
|---|--|--|--|--|
| Ac | | | | |
| Overall Length: | | | | |
| 2.781 inches | | | | |
| Scale Division Quantity: | | | | |
| 5 single indicator single range | | | | |
| Overall Diameter: | | | | |
| 3.500 inches | | | | |
| Indicator Type: | | | | |
| Dial w/pointer | | | | |
| Installation Design: | | | | |
| Panel | | | | |
| Sensitivity Rating: | | | | |
| 1600.0 microamperes | | | | |
| Dial Scale Marking Color: | | | | |
| Silver single indicator single range | | | | |
| Accuracy In Percent: | | | | |
| -5.0 to 5.0 at full scale single indicator single range | | | | |
| Meter Depth Behind Mounting Flange: | | | | |
| 1.670 inches | | | | |
| Meter Body Diameter Behind Mounting Flange: | | | | |
| 2.800 inches | | | | |
| Movement Type: | | | | |
| Electrodynamometer | | | | |
| Background Color: | | | | |
| Black single indicator single range | | | | |
| Pointer Color: | | | | |
| Black single indicator single range | | | | |
| Scale Marking: | | | | |
| Marked in four parts | | | | |
| Mounting Facility Type And Quantity: | | | | |
| 2 bushing | | | | |
| Scale Graduation Type: | | | | |
| Linear single indicator single range | | | | |
| Features Provided: | | | | |
| Zero adjuster | | | | |
| Circuit Attachment Method And Quantity: | | | | |
| 2 threaded stud | | | | |
| Special Features: | | | | |
| Ruggedized | | | | |
| Material: | | | | |
| | | | | |

NSN 6625-00-250-7021

Arbitrary Scale Meter - Page 2 of 2



| Nucle | ar Hardne | ss Critica | I Feature: |
|--------|-------------|------------|--------------|
| INUCIE | ai ilaiulle | เออ บานเบอ | II I CALUIC. |

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0