# NSN 6625-00-252-4342

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-252-4342

# **Circuit Current For Which Designed:**

Ac

# Dielectric Withstanding Voltage In Volts:

1500.0

# Overall Length:

1.968 inches

# Center To Center Distance Between Mounting Facilities Parallel To Length:

1.906 inches

# Center To Center Distance Between Mounting Facilities Parallel To Width:

1.906 inches

## **Overall Height:**

2.375 inches

# Overall Width:

2.375 inches

## Mounting Stud Length:

0.500 inches

#### **Environmental Protection:**

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

#### Furnished Items And Quantity:

Nut 6; lockwasher 6; seal 1

#### Indicator Type:

Dial w/pointer

#### Installation Design:

Panel

#### Mounting Arrangement Style:

Four hole/stud rectangular/square

#### Sensitivity Rating:

14.0 millivolts

#### **Dial Scale Marking Color:**

Black single indicator single range

#### Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

#### Meter Depth Behind Mounting Flange:

1.125 inches

#### Meter Body Diameter Behind Mounting Flange:

2.156 inches

#### Movement Type:

Moving coil, permanent magnet

#### **Background Color:**

White single indicator single range

#### Pointer Color:

Black single indicator single range

# NSN 6625-00-252-4342

Ammeter - Page 2 of 2



Power Source:	
External	
Mounting Facility Type And Quantity:	
4 threaded stud	
Scale Graduation Type:	
Nonlinear single indicator single range	
Measurement Range:	
+0.0/+3.0 amperes, ac single indicator single range	
Mounting Stud Diameter:	
0.125 inches	
Scale Selection Method:	
Terminal	
Features Provided:	
Zero adjuster	
Movement Suspension Method:	
Jewel pivot base	
Circuit Attachment Method And Quantity:	
2 threaded stud	
Special Features:	
Ruggedized	
Special Markings:	
On face, thermo couple type	
Material:	
Plastic	
Nuclear Hardness Critical Feature:	
Nonhardened	
Surface Treatment:	
Paint	
Special Test Features:	
Complies with mil-m-10304	
Style Designator:	
Rectangular flush mtg	
Fsc Application Data:	
Test set, elect. Equip.	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A310a0	