NSN 6625-00-253-9199

Audio Level Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-253-9199

| Circuit Current For Which Designed: |
|---|
| Dc |
| Overall Length: |
| 2.880 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.250 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.250 inches |
| Overall Height: |
| 3.150 inches |
| Overall Width: |
| 3.130 inches |
| Scale Division Quantity: |
| 5 single indicator single range |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0 to 2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.125 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 3.250 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Power Source: |
| External |
| Mounting Facility Type And Quantity: |
| 4 threaded stud |
| Scale Graduation Type: |
| Linear single indicator single range |

Measurement Range:

+0.0 to 20.0 decibels single indicator single range

NSN 6625-00-253-9199

Audio Level Meter - Page 2 of 2



| Mounting Stud Diameter: |
|---|
| 0.112 inches |
| Features Provided: |
| Self-illumination facility |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud and 2 wire wrap |
| Material: |
| Plastic |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Rectangular flush mtg |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| 4310a0 |
| |