NSN 6625-00-264-5180



| Ammeter - Page 1 of 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/6625-00-264-5180 |
| Circuit Current For Which Designed: |
| Dc |
| Overall Length: |
| 2.650 inches |
| Scale Division Quantity: |
| 50 single indicator single range |
| Mounting Stud Length: |
| Between 0.375 inches and 0.625 inches |
| Overall Diameter: |
| 2.695 inches |
| Mounting Bolt Circle Diameter: |
| 2.436 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -1.0/+1.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 2.250 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.210 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+3.0 amperes, dc single indicator single range

Mounting Stud Diameter:

0.112 inches

NSN 6625-00-264-5180

Ammeter - Page 2 of 2



| Features Provided: | | | |
|---|--|--|--|
| Zero adjuster | | | |
| Movement Suspension Method: | | | |
| Jewel pivot base | | | |
| Circuit Attachment Method And Quantity: | | | |
| 2 solder lug | | | |
| Material: | | | |
| Plastic | | | |
| Nuclear Hardness Critical Feature: | | | |
| Nonhardened | | | |
| Style Designator: | | | |
| Round flush mtg | | | |
| Fsc Application Data: | | | |
| Test set electronic | | | |
| Shelf Life: | | | |
| N/a | | | |
| Unit Of Measure: | | | |
| | | | |
| Demilitarization: | | | |
| No | | | |
| Fiig: | | | |
| A310a0 | | | |
| | | | |