## NSN 6625-00-264-7997

**Circuit Current For Which Designed:** 

Electrical Frequency Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-264-7997

Ac
Overall Length:
2.740 inches
Mounting Hole Diameter:
0.147 inches
Scale Division Quantity:
6 single indicator single range
Overall Diameter:
3.500 inches
Environmental Protection:
Shock resistant and vibration resistant
Mounting Bolt Circle Diameter:
3.160 inches
Furnished Items And Quantity:
Nut 4
Indicator Type:
Vibrating reed
Installation Design:
Panel
Register Quantity:
1
Mounting Arrangement Style:
Three hole/stud bolt circle
Three hole/stud bolt circle  Resonant Reed Quantity:
Resonant Reed Quantity:
Resonant Reed Quantity:
Resonant Reed Quantity: 7 Meter Depth Behind Mounting Flange:
Resonant Reed Quantity: 7 Meter Depth Behind Mounting Flange: 1.930 inches
Resonant Reed Quantity: 7 Meter Depth Behind Mounting Flange: 1.930 inches Meter Body Diameter Behind Mounting Flange:
Resonant Reed Quantity: 7 Meter Depth Behind Mounting Flange: 1.930 inches Meter Body Diameter Behind Mounting Flange: 2.780 inches
Resonant Reed Quantity: 7 Meter Depth Behind Mounting Flange: 1.930 inches Meter Body Diameter Behind Mounting Flange: 2.780 inches Movement Type:
Resonant Reed Quantity: 7 Meter Depth Behind Mounting Flange: 1.930 inches Meter Body Diameter Behind Mounting Flange: 2.780 inches Movement Type: Vibrating reed
Resonant Reed Quantity: 7 Meter Depth Behind Mounting Flange: 1.930 inches Meter Body Diameter Behind Mounting Flange: 2.780 inches Movement Type: Vibrating reed Background Color:
Resonant Reed Quantity: 7 Meter Depth Behind Mounting Flange: 1.930 inches Meter Body Diameter Behind Mounting Flange: 2.780 inches Movement Type: Vibrating reed Background Color: White single indicator single range
Resonant Reed Quantity: 7 Meter Depth Behind Mounting Flange: 1.930 inches Meter Body Diameter Behind Mounting Flange: 2.780 inches Movement Type: Vibrating reed Background Color: White single indicator single range Pointer Color:
Resonant Reed Quantity: 7  Meter Depth Behind Mounting Flange: 1.930 inches  Meter Body Diameter Behind Mounting Flange: 2.780 inches  Movement Type: Vibrating reed  Background Color: White single indicator single range  Pointer Color: Black single indicator single range
Resonant Reed Quantity: 7  Meter Depth Behind Mounting Flange: 1.930 inches  Meter Body Diameter Behind Mounting Flange: 2.780 inches  Movement Type: Vibrating reed  Background Color: White single indicator single range  Pointer Color: Black single indicator single range  Power Source:
Resonant Reed Quantity: 7  Meter Depth Behind Mounting Flange: 1.930 inches  Meter Body Diameter Behind Mounting Flange: 2.780 inches  Movement Type: Vibrating reed  Background Color: White single indicator single range  Pointer Color: Black single indicator single range  Power Source: External
Resonant Reed Quantity: 7  Meter Depth Behind Mounting Flange: 1.930 inches  Meter Body Diameter Behind Mounting Flange: 2.780 inches  Movement Type: Vibrating reed  Background Color: White single indicator single range  Pointer Color: Black single indicator single range  Power Source: External  Mounting Facility Type And Quantity:

## NSN 6625-00-264-7997

Electrical Frequency Meter - Page 2 of 2



Measurement Range:
+57.0 to 63.0 hertz single indicator single range
Circuit Attachment Method And Quantity:
2 threaded stud and 2 solder lug
Operating Voltage Rating In Volts:
Between 100.0 ac and 150.0 ac
Special Features:
Ruggedized
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A310a0