

View Online at <https://aerobasegroup.com/nsn/6625-00-264-7997>

Circuit Current For Which Designed:

Ac

Overall Length:

2.740 inches

Mounting Hole Diameter:

0.147 inches

Scale Division Quantity:

6 single indicator single range

Overall Diameter:

3.500 inches

Environmental Protection:

Shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Nut 4

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Resonant Reed Quantity:

7

Meter Depth Behind Mounting Flange:

1.930 inches

Meter Body Diameter Behind Mounting Flange:

2.780 inches

Movement Type:

Vibrating reed

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+57.0 to 63.0 hertz single indicator single range

Circuit Attachment Method And Quantity:

2 threaded stud and 2 solder lug

Operating Voltage Rating In Volts:

Between 100.0 ac and 150.0 ac

Special Features:

Ruggedized

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0