

View Online at <https://aerobasegroup.com/nsn/6625-00-264-8026>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.969 inches

Mounting Hole Diameter:

0.150 inches

Overall Diameter:

3.500 inches

Environmental Protection:

Dust resistant and hermetic and humidity resistant and vibration resistant

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Nut 5; washer 5

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

1.0 watts

Dial Scale Marking Color:

White single indicator single range

Resonant Reed Quantity:

5

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

2.250 inches

Meter Body Diameter Behind Mounting Flange:

2.688 inches

Movement Type:

Vibrating reed

Background Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Measurement Range:

+58.0 to 62.0 hertz single indicator single range

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Special Markings:

Hertz

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Style Designator:

Round flush mtg

Fsc Application Data:

Electrical, electronic properties measuring and test instruments

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0