

View Online at <https://aerobasegroup.com/nsn/6625-00-271-9120>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

4000.0

Overall Length:

3.187 inches

Overall Height:

1.000 inches

Overall Width:

3.250 inches

Mounting Hole Diameter:

0.125 inches

Environmental Protection:

Shock resistant and vibration resistant

Distance Between Mounting Facility Centers:

2.875 inches

Barrel Width:

1.625 inches

Furnished Items And Quantity:

Bezel 1, screw 2, nut 2, washer 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.578 inches

Meter Body Width Behind Mounting Flange:

2.578 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 screw and 2 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+5.0 milliamperes, dc single indicator single range

Meter Body Height Behind Mounting Flange:

1.343 inches

Meter Barrel Depth:

1.625 inches

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Ruggedized

Material:

Plastic polycarbonate

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg barrel, right

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0