## NSN 6625-00-281-2397

Ammeter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-00-281-2397

Circuit Current For Which Designed:

Overall Length: 2.500 inches Overall Height: 4.000 inches Overall Width: 4.625 inches Distance Between Mounting Facility Centers: 3.750 inches Installation Design: Panel Mounting Arrangement Style: Two hole/stud Meter Depth Behind Mounting Flange: 1.922 inches Meter Body Diameter Behind Mounting Flange: 2.790 inches Mounting Facility Type And Quantity: 2 threaded stud Measurement Range: +0.0/+500.0 milliamperes, dc single indicator 1st range Scale Selection Method: Terminal Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 threaded stud and 2 solder lug Style Designator: Rectangular flush mtg	Circuit Current For Which Designed:
2.500 inches  Overall Height: 4.000 inches  Overall Width: 4.625 inches  Distance Between Mounting Facility Centers: 3.750 inches Installation Design: Panel  Mounting Arrangement Style: Two hole/stud  Meter Depth Behind Mounting Flange: 1.922 inches  Meter Body Diameter Behind Mounting Flange: 2.790 inches  Mounting Facility Type And Quantity: 2 threaded stud  Measurement Range: +0.0/+500.0 milliamperes, dc single indicator 1st range Scale Selection Method: Terminal  Movement Suspension Method: Taut band  Circuit Attachment Method And Quantity: 2 threaded stud and 2 solder lug  Style Designator: Rectangular flush mtg	Dc
Overall Height: 4.000 inches Overall Width: 4.625 inches Distance Between Mounting Facility Centers: 3.750 inches Installation Design: Panel Mounting Arrangement Style: Two hole/stud Meter Depth Behind Mounting Flange: 1.922 inches Meter Body Diameter Behind Mounting Flange: 2.790 inches Mounting Facility Type And Quantity: 2 threaded stud Measurement Range: +0.0/+500.0 milliamperes, dc single indicator 1st range Scale Selection Method: Terminal Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 threaded stud and 2 solder lug Style Designator: Rectangular flush mtg	Overall Length:
4.000 inches Overall Width: 4.625 inches Distance Between Mounting Facility Centers: 3.750 inches Installation Design: Panel Mounting Arrangement Style: Two hole/stud Meter Depth Behind Mounting Flange: 1.922 inches Meter Body Diameter Behind Mounting Flange: 2.790 inches Mounting Facility Type And Quantity: 2 threaded stud Measurement Range: +0.0/+500.0 milliamperes, dc single indicator 1st range Scale Selection Method: Terminal Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 threaded stud and 2 solder lug Style Designator: Rectangular flush mtg	2.500 inches
Overall Width: 4.625 inches Distance Between Mounting Facility Centers: 3.750 inches Installation Design: Panel Mounting Arrangement Style: Two hole/stud Meter Depth Behind Mounting Flange: 1.922 inches Meter Body Diameter Behind Mounting Flange: 2.790 inches Mounting Facility Type And Quantity: 2 threaded stud Measurement Range: +0.0/+500.0 milliamperes, dc single indicator 1st range Scale Selection Method: Terminal Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 threaded stud and 2 solder lug Style Designator: Rectangular flush mtg	Overall Height:
4.625 inches  Distance Between Mounting Facility Centers: 3.750 inches Installation Design: Panel Mounting Arrangement Style: Two hole/stud Meter Depth Behind Mounting Flange: 1.922 inches Meter Body Diameter Behind Mounting Flange: 2.790 inches Mounting Facility Type And Quantity: 2 threaded stud Measurement Range: +0.0/+500.0 milliamperes, dc single indicator 1st range Scale Selection Method: Terminal Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 threaded stud and 2 solder lug Style Designator: Rectangular flush mtg	4.000 inches
Distance Between Mounting Facility Centers:  3.750 inches Installation Design: Panel Mounting Arrangement Style: Two hole/stud Meter Depth Behind Mounting Flange: 1.922 inches Meter Body Diameter Behind Mounting Flange: 2.790 inches Mounting Facility Type And Quantity: 2 threaded stud Measurement Range: +0.0/+500.0 milliamperes, dc single indicator 1st range Scale Selection Method: Terminal Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 threaded stud and 2 solder lug Style Designator: Rectangular flush mtg	Overall Width:
Installation Design: Panel Mounting Arrangement Style: Two hole/stud Meter Depth Behind Mounting Flange: 1.922 inches Meter Body Diameter Behind Mounting Flange: 2.790 inches Mounting Facility Type And Quantity: 2 threaded stud Measurement Range: +0.0/+500.0 milliamperes, dc single indicator 1st range Scale Selection Method: Terminal Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 threaded stud and 2 solder lug Style Designator: Rectangular flush mtg	4.625 inches
Installation Design: Panel Mounting Arrangement Style: Two hole/stud Meter Depth Behind Mounting Flange: 1.922 inches Meter Body Diameter Behind Mounting Flange: 2.790 inches Mounting Facility Type And Quantity: 2 threaded stud Measurement Range: +0.0/+500.0 milliamperes, dc single indicator 1st range Scale Selection Method: Terminal Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 threaded stud and 2 solder lug Style Designator: Rectangular flush mtg	Distance Between Mounting Facility Centers:
Mounting Arrangement Style: Two hole/stud Meter Depth Behind Mounting Flange: 1.922 inches Meter Body Diameter Behind Mounting Flange: 2.790 inches Mounting Facility Type And Quantity: 2 threaded stud Measurement Range: +0.0/+500.0 milliamperes, dc single indicator 1st range Scale Selection Method: Terminal Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 threaded stud and 2 solder lug Style Designator: Rectangular flush mtg	3.750 inches
Mounting Arrangement Style: Two hole/stud  Meter Depth Behind Mounting Flange: 1.922 inches  Meter Body Diameter Behind Mounting Flange: 2.790 inches  Mounting Facility Type And Quantity: 2 threaded stud  Measurement Range: +0.0/+500.0 milliamperes, dc single indicator 1st range  Scale Selection Method: Terminal  Movement Suspension Method: Taut band  Circuit Attachment Method And Quantity: 2 threaded stud and 2 solder lug  Style Designator: Rectangular flush mtg	Installation Design:
Two hole/stud  Meter Depth Behind Mounting Flange: 1.922 inches  Meter Body Diameter Behind Mounting Flange: 2.790 inches  Mounting Facility Type And Quantity: 2 threaded stud  Measurement Range: +0.0/+500.0 milliamperes, dc single indicator 1st range  Scale Selection Method: Terminal  Movement Suspension Method: Taut band  Circuit Attachment Method And Quantity: 2 threaded stud and 2 solder lug  Style Designator: Rectangular flush mtg	Panel
Meter Depth Behind Mounting Flange:  1.922 inches  Meter Body Diameter Behind Mounting Flange:  2.790 inches  Mounting Facility Type And Quantity:  2 threaded stud  Measurement Range: +0.0/+500.0 milliamperes, dc single indicator 1st range  Scale Selection Method:  Terminal  Movement Suspension Method:  Taut band  Circuit Attachment Method And Quantity:  2 threaded stud and 2 solder lug  Style Designator:  Rectangular flush mtg	Mounting Arrangement Style:
1.922 inches  Meter Body Diameter Behind Mounting Flange: 2.790 inches  Mounting Facility Type And Quantity: 2 threaded stud  Measurement Range: +0.0/+500.0 milliamperes, dc single indicator 1st range  Scale Selection Method: Terminal  Movement Suspension Method: Taut band  Circuit Attachment Method And Quantity: 2 threaded stud and 2 solder lug  Style Designator: Rectangular flush mtg	Two hole/stud
Meter Body Diameter Behind Mounting Flange: 2.790 inches  Mounting Facility Type And Quantity: 2 threaded stud  Measurement Range: +0.0/+500.0 milliamperes, dc single indicator 1st range  Scale Selection Method: Terminal  Movement Suspension Method: Taut band  Circuit Attachment Method And Quantity: 2 threaded stud and 2 solder lug  Style Designator: Rectangular flush mtg	Meter Depth Behind Mounting Flange:
2.790 inches  Mounting Facility Type And Quantity: 2 threaded stud  Measurement Range: +0.0/+500.0 milliamperes, dc single indicator 1st range Scale Selection Method: Terminal  Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 threaded stud and 2 solder lug Style Designator: Rectangular flush mtg	1.922 inches
Mounting Facility Type And Quantity:  2 threaded stud  Measurement Range: +0.0/+500.0 milliamperes, dc single indicator 1st range Scale Selection Method: Terminal  Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 threaded stud and 2 solder lug  Style Designator: Rectangular flush mtg	Meter Body Diameter Behind Mounting Flange:
2 threaded stud  Measurement Range: +0.0/+500.0 milliamperes, dc single indicator 1st range  Scale Selection Method: Terminal  Movement Suspension Method: Taut band  Circuit Attachment Method And Quantity: 2 threaded stud and 2 solder lug  Style Designator: Rectangular flush mtg	2.790 inches
Measurement Range: +0.0/+500.0 milliamperes, dc single indicator 1st range Scale Selection Method: Terminal Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 threaded stud and 2 solder lug Style Designator: Rectangular flush mtg	Mounting Facility Type And Quantity:
+0.0/+500.0 milliamperes, dc single indicator 1st range Scale Selection Method: Terminal Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 threaded stud and 2 solder lug Style Designator: Rectangular flush mtg	2 threaded stud
Scale Selection Method: Terminal Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 threaded stud and 2 solder lug Style Designator: Rectangular flush mtg	Measurement Range:
Terminal  Movement Suspension Method:  Taut band  Circuit Attachment Method And Quantity:  2 threaded stud and 2 solder lug  Style Designator:  Rectangular flush mtg	+0.0/+500.0 milliamperes, $\ dc \ single \ indicator \ 1st \ range$
Movement Suspension Method:  Taut band  Circuit Attachment Method And Quantity:  2 threaded stud and 2 solder lug  Style Designator:  Rectangular flush mtg	Scale Selection Method:
Taut band  Circuit Attachment Method And Quantity: 2 threaded stud and 2 solder lug  Style Designator:  Rectangular flush mtg	Terminal
Circuit Attachment Method And Quantity: 2 threaded stud and 2 solder lug Style Designator: Rectangular flush mtg	Movement Suspension Method:
2 threaded stud and 2 solder lug  Style Designator:  Rectangular flush mtg	Taut band
Style Designator: Rectangular flush mtg	Circuit Attachment Method And Quantity:
Rectangular flush mtg	2 threaded stud and 2 solder lug
	Style Designator:
	Rectangular flush mtg
Shelf Life:	Shelf Life:
N/a	N/a
Unit Of Measure:	Unit Of Measure:

**Demilitarization:** No

Fiig:

A310a0