

View Online at <https://aerobasegroup.com/nsn/6625-00-283-9621>

**Mounting Type:**

Rack

**Current Type:**

Ac

**Frequency Rating:**

Between 50.0 hertz and 1.6 kilohertz

**Frequency Range Rating:**

+0.900/+2.100 gigahertz

**Accessory Component Quantity:**

1 and 1 and 1 and 1 and 1 and 2 and 3 and 3 and 3 and 3 and 5 and 1

**Accessory Controlling Agency:**

Buships; buships; bauer; buships; buships; bauer; gusaf; gusaf; gusaf; general electric co; western electric co

**Accessory Identifying Number:**

Ts-419/u type no. And ct-686/u type no. And cx-337/u type no. And cx-337/u type no. And cg-546/u 6 ft type no. And cg409/u 6 ft type no. And ug-201/u type no. And ug-225/u type no. And ug-273/u type no. And 47 type no. And not applicable type no. And 166382 type no.

**Internal Battery Accommodation:**

Not included

**Output Impedance Rating:**

50.0 ohms

**Voltage Rating:**

115.0 volts

**Frequency Band Quantity:**

1

**Modulation Type:**

Pulse and pulse

**Accessory Component Name:**

Sig generator; case; cord; rf cable assembly; rf cable assembly; cord; adapter; adapter; adapter; indicator lamps; fuse 3 amp; thermistor bead

**Calibration Accuracy Rating:**

1 pct

**Crystal Controlled Feature:**

Not provided

**Calibrated Signal Output Range:**

0.16 v to 0.2 uv

**Signal Output Constancy:**

Porm 2db maximum variation

**Modulator Location:**

Any acceptable

**Pulse Repetition Frequency Rating:**

Between 40.0 hertz and 4.0 kilohertz

**Modulation Degree:**

100.0 percent

**Phase:**

Single

**Special Features:**

Case material and surface treatment per specification 16t35 /re/

**Specification Or Standard:**

An/urm-64 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

T320-j