

View Online at <https://aerobasegroup.com/nsn/6625-00-283-9621>

Mounting Type:

Rack

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 1.6 kilohertz

Frequency Range Rating:

+0.900/+2.100 gigahertz

Accessory Component Quantity:

1 and 1 and 1 and 1 and 1 and 2 and 3 and 3 and 3 and 3 and 5 and 1

Accessory Controlling Agency:

Buships; buships; bauer; buships; buships; bauer; gusaf; gusaf; gusaf; general electric co; western electric co

Accessory Identifying Number:

Ts-419/u type no. And ct-686/u type no. And cx-337/u type no. And cx-337/u type no. And cg-546/u 6 ft type no. And cg409/u 6 ft type no. And ug-201/u type no. And ug-225/u type no. And ug-273/u type no. And 47 type no. And not applicable type no. And 166382 type no.

Internal Battery Accommodation:

Not included

Output Impedance Rating:

50.0 ohms

Voltage Rating:

115.0 volts

Frequency Band Quantity:

1

Modulation Type:

Pulse and pulse

Accessory Component Name:

Sig generator; case; cord; rf cable assembly; rf cable assembly; cord; adapter; adapter; adapter; indicator lamps; fuse 3 amp; thermistor bead

Calibration Accuracy Rating:

1 pct

Crystal Controlled Feature:

Not provided

Calibrated Signal Output Range:

0.16 v to 0.2 uv

Signal Output Constancy:

Porm 2db maximum variation

Modulator Location:

Any acceptable

Pulse Repetition Frequency Rating:

Between 40.0 hertz and 4.0 kilohertz

Modulation Degree:

100.0 percent

Phase:

Single

Special Features:

Case material and surface treatment per specification 16t35 /re/

Specification Or Standard:

An/urm-64 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T320-j