

View Online at <https://aerobasegroup.com/nsn/6625-00-291-0900>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

3.790 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 3.799 inches and 3.811 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 0.744 inches and 0.756 inches

Overall Height:

1.525 inches

Overall Width:

4.234 inches

Mounting Hole Diameter:

0.138 inches

Environmental Protection:

Shock resistant and vibration resistant and watertight

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

1.8 milliamperes and 18.5 milliamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-3.0 to 3.0 at full scale single indicator 4th range

Meter Depth Behind Mounting Flange:

Between 2.525 inches and 3.603 inches

Meter Body Width Behind Mounting Flange:

3.450 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

-10.0 to 0.0 decibels above or below one milliwatt single indicator 1st range

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

1.525 inches

Features Provided:

Knife edge pointer and magnetic shield and self-illumination facility and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Ruggedized and horizontal mounting

Material:

Aluminum

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Special Test Features:

Drawing iaw mil-d-1000; shock and moisture resistant iaw mil-std-202; mark iaw mil-std-130

Style Designator:

Rectangular flush mtg

Supplementary Features:

Internal res upper scale 18 ohms porm 5 pct; lower scale 135 ohms porm 5 pct; response time 2 sec

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0