

View Online at <https://aerobasegroup.com/nsn/6625-00-291-0920>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

150.0

Overall Length:

6.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.000 inches

Overall Height:

1.280 inches

Overall Width:

2.630 inches

Mounting Hole Diameter:

0.112 inches

Environmental Protection:

Shock resistant and vibration resistant

Indicator Type:

Digital display

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Meter Depth Behind Mounting Flange:

4.800 inches

Meter Body Width Behind Mounting Flange:

2.040 inches

Background Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 unthreaded hole

Display Type:

Light emitting diode (I.E.D.).

Display Digit Quantity:

3

Measurement Range:

-1.999 to 1.999 volts single indicator single range

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

1.280 inches

Features Provided:

Overranging

Accuracy Rating:

Porm 0.2 pct of reading porm 1 digit single indicator single range

Display Color:

Red single indicator single range

Circuit Attachment Method And Quantity:

2 connector, plug

Operating Voltage Rating In Volts:

5.0 dc

Special Features:

Overrange light for 1 to 1.999

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Supplementary Features:

1000 megohms resistance

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0