

View Online at <https://aerobasegroup.com/nsn/6625-00-291-0937>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Overall Length:**

3.790 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 3.799 inches and 3.811 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

Between 0.744 inches and 0.756 inches

**Overall Height:**

1.525 inches

**Overall Width:**

4.234 inches

**Mounting Hole Diameter:**

0.138 inches

**Environmental Protection:**

Shock resistant and vibration resistant and watertight

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

1.85 milliamperes and 18.5 milliamperes

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

Between 2.525 inches and 2.603 inches

**Meter Body Width Behind Mounting Flange:**

3.450 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Scale Graduation Type:**

Nonlinear single indicator all ranges

**Measurement Range:**

-10.0 to 0.0 decibels above or below one milliwatt single indicator 2nd range

**Scale Selection Method:**

Terminal

**Meter Body Height Behind Mounting Flange:**

1.525 inches

**Features Provided:**

Knife edge pointer and magnetic shield and self-illumination facility and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder lug

**Special Features:**

Ruggedized and horizontal mounting

**Special Markings:**

Track pk pwr on 0 to 800 kw range; capt./guid. Pk pwr on 0 to 350 kw range; pulse sim. On dbm ranges

**Material:**

Aluminum

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Special Test Features:**

Drawing iaw mil-d-1000; shock and moisture resistant iaw mil-std-202; mark iaw mil-std-130

**Style Designator:**

Rectangular flush mtg

**Supplementary Features:**

18 ohm upper and 135 ohm lower range resistances

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A310a0