

View Online at <https://aerobasegroup.com/nsn/6625-00-291-0937>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

3.790 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 3.799 inches and 3.811 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 0.744 inches and 0.756 inches

Overall Height:

1.525 inches

Overall Width:

4.234 inches

Mounting Hole Diameter:

0.138 inches

Environmental Protection:

Shock resistant and vibration resistant and watertight

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

1.85 milliamperes and 18.5 milliamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

Between 2.525 inches and 2.603 inches

Meter Body Width Behind Mounting Flange:

3.450 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

-10.0 to 0.0 decibels above or below one milliwatt single indicator 2nd range

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

1.525 inches

Features Provided:

Knife edge pointer and magnetic shield and self-illumination facility and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Ruggedized and horizontal mounting

Special Markings:

Track pk pwr on 0 to 800 kw range; capt./guid. Pk pwr on 0 to 350 kw range; pulse sim. On dbm ranges

Material:

Aluminum

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Special Test Features:

Drawing iaw mil-d-1000; shock and moisture resistant iaw mil-std-202; mark iaw mil-std-130

Style Designator:

Rectangular flush mtg

Supplementary Features:

18 ohm upper and 135 ohm lower range resistances

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0