

View Online at <https://aerobasegroup.com/nsn/6625-00-301-0231>

Circuit Current For Which Designed:

Dc

Reliability Indicator:

Established

Overall Length:

2.141 inches

Overall Height:

0.776 inches

Overall Width:

1.872 inches

Mounting Hole Diameter:

0.086 inches

Scale Division Quantity:

20 single indicator single range

Environmental Protection:

Shock resistant and vibration resistant

Distance Between Mounting Facility Centers:

1.285 inches

Barrel Width:

1.605 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.932 inches

Meter Body Width Behind Mounting Flange:

1.605 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 bezel and 2 threaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+1.0 milliamperes, dc single indicator single range

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

1.602 inches

Meter Barrel Depth:

1.421 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solderless lug

Special Features:

Ruggedized

Special Markings:

Red band 0 to 0.1 ma; yellow to 0.5; green to 0.9; red to 1

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg barrel, left

Fsc Application Data:

Electrical and electronic properties measuring and testing instruments

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0