

View Online at <https://aerobasegroup.com/nsn/6625-00-308-2725>

Circuit Current For Which Designed:

Dc

Overall Length:

2.870 inches

Mounting Hole Diameter:

0.201 inches

Overall Diameter:

4.560 inches

Mounting Bolt Circle Diameter:

4.120 inches

Furnished Items And Quantity:

Nut 9; lock washer 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Six hole/stud bolt circle

Sensitivity Rating:

500.0 microamperes and 300.0 volts

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-1.0 to 1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.710 inches

Meter Body Diameter Behind Mounting Flange:

3.650 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black, dull single indicator single range

Pointer Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0 to 6.0 decibels single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

3 solder lug and 3 threaded stud

Special Markings:

Positive terminal has plus sign by it; negative terminal has com under it; sealed do not open on back of meter

Material:

Copper alloy

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0