

View Online at <https://aerobasegroup.com/nsn/6625-00-308-2725>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

2.870 inches

**Mounting Hole Diameter:**

0.201 inches

**Overall Diameter:**

4.560 inches

**Mounting Bolt Circle Diameter:**

4.120 inches

**Furnished Items And Quantity:**

Nut 9; lock washer 3

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Six hole/stud bolt circle

**Sensitivity Rating:**

500.0 microamperes and 300.0 volts

**Dial Scale Marking Color:**

White single indicator single range

**Accuracy In Percent:**

-1.0 to 1.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.710 inches

**Meter Body Diameter Behind Mounting Flange:**

3.650 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

Black, dull single indicator single range

**Pointer Color:**

White single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 screw and 3 unthreaded hole

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

+0.0 to 6.0 decibels single indicator single range

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

3 solder lug and 3 threaded stud

**Special Markings:**

Positive terminal has plus sign by it; negative terminal has com under it; sealed do not open on back of meter

**Material:**

Copper alloy

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiq:**

A310a0