

View Online at <https://aerobasegroup.com/nsn/6625-00-318-3591>

Circuit Current For Which Designed:

Dc

Overall Length:

6.937 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.422 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.422 inches

Overall Height:

4.422 inches

Overall Width:

4.422 inches

Scale Division Quantity:

50 single indicator single range

Mounting Stud Length:

0.625 inches

Environmental Protection:

Dustproof

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0 to 1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

5.250 inches

Meter Body Diameter Behind Mounting Flange:

3.960 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 100.0 millivolts, dc single indicator single range

Mounting Stud Diameter:

0.250 inches

Scale Selection Method:

Switch

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel lusterless

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set electronic

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0