NSN 6625-00-318-3592

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-318-3592

| Circuit Current For Which Designed: |
|---|
| Ac |
| Overall Length: |
| 7.218 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.375 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.375 inches |
| Overall Height: |
| 4.794 inches |

Overall Width:

4.794 inches

Scale Division Quantity:

40 single indicator single range

Mounting Stud Length:

0.625 inches

Environmental Protection:

Dustproof

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

3.750 inches

Meter Body Diameter Behind Mounting Flange:

3.960 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

NSN 6625-00-318-3592

Ammeter - Page 2 of 2



Scale Graduation Type: Linear single indicator single range **Measurement Range:** +0.0/+200.0 amperes, ac single indicator single range Mounting Stud Diameter: 0.250 inches **Features Provided:** Zero adjuster **Movement Suspension Method:** Taut band **Circuit Attachment Method And Quantity:** 2 threaded stud Material: Plastic phenolic **Nuclear Hardness Critical Feature:** Nonhardened Surface Treatment: Enamel semigloss Style Designator: Rectangular flush mtg **Fsc Application Data:** Test set electronic Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A310a0