NSN 6625-00-324-8827

Ammeter - Page 1 of 2

External

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-324-8827

| Dc |
|---|
| Overall Length: |
| 1.375 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.250 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.250 inches |
| Overall Height: |
| 3.000 inches |
| Overall Width: |
| 3.000 inches |
| Mounting Hole Diameter: |
| 0.112 inches |
| Scale Division Quantity: |
| 50 single indicator single range |
| Environmental Protection: |
| Dustproof |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Sensitivity Rating: |
| 53.0 millivolts |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.125 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.795 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Power Source: |

NSN 6625-00-324-8827

Ammeter - Page 2 of 2



| Mounting Facility Type And Quantity: |
|--|
| 4 unthreaded hole |
| Scale Graduation Type: |
| Linear single indicator single range |
| Measurement Range: |
| +0.0/+1.0 milliamperes, dc single indicator single range |
| Features Provided: |
| Zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 solder stud |
| Material: |
| Plastic |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Rectangular flush mtg |
| Fsc Application Data: |
| Test set electronic |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| . |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |
| |