

View Online at <https://aerobasegroup.com/nsn/6625-00-324-8827>

Circuit Current For Which Designed:

Dc

Overall Length:

1.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches

Overall Height:

3.000 inches

Overall Width:

3.000 inches

Mounting Hole Diameter:

0.112 inches

Scale Division Quantity:

50 single indicator single range

Environmental Protection:

Dustproof

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

53.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.125 inches

Meter Body Diameter Behind Mounting Flange:

2.795 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+1.0 milliamperes, dc single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set electronic

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0