

View Online at <https://aerobasegroup.com/nsn/6625-00-327-6585>

Circuit Current For Which Designed:

Dc

Overall Depth:

3.000 inches

Overall Length:

9.000 inches

Overall Width:

6.190 inches

Scale Division Quantity:

1 single indicator single range

Frequency Rating:

Between 5.0 hertz and 100.0 kilohertz

End Application:

Electronic test equipment

Furnished Items And Quantity:

4 alkaline energizer c cell batteries; microphone attenuator, tool kit, 10 ft microphone extension cable, windscreen

Indicator Type:

Dial w/pointer

Installation Design:

Hand held

Dial Scale Marking Color:

White single indicator single range

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Power Source:

Internal

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+10.0 to 30.0 decibels single indicator single range

Features Provided:

Internal battery accommodation and portable

Special Features:

Opt 9712 includes cables: 1933-9602, 1560-9677, 1560-9678, 1560-9679, 1933-9601; windscreens: 1560-9521 and 1560-9522; microphone pn 1560-9609; calibrator set pn 1562-9701, case pn 1933-9604; tripod 1560-9590; octave bands w/center frequency 31.5 hz to 16.0 khz; level range: 10 db to 130 db re 20 upa w/1 in. Microphone, 20 db to 140 db w/ 1/2 in. Microphone; operating temperature: m 10.0/p 50.0 deg. C; storage temp.: m 40.0/p 60.0 deg. C w/batteries removed

Reference Data And Literature:

Genrad catalog

Style Designator:

Hand-held

Reference Number Differentiating Characteristics:

As differentiated by the accessories included

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0