

View Online at <https://aerobasegroup.com/nsn/6625-00-330-6947>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

2.350 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 2.730 inches and 2.750 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

Between 2.363 inches and 2.383 inches

**Overall Height:**

3.500 inches

**Overall Width:**

3.500 inches

**Mounting Stud Length:**

0.500 inches

**Shortest Horizontal Distance Between Mounting Centers:**

Between 1.360 inches and 1.380 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud triangular

**Frequency Response Range:**

+25.000/+400.000 hertz

**Meter Depth Behind Mounting Flange:**

1.210 inches

**Meter Body Diameter Behind Mounting Flange:**

2.700 inches

**Movement Type:**

Moving iron vane

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 threaded stud

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

+0.0/+150.0 amperes, ac single indicator single range

**Mounting Stud Diameter:**

0.112 inches

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0