

View Online at <https://aerobasegroup.com/nsn/6625-00-344-1803>

Circuit Current For Which Designed:

Dc

Overall Length:

5.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches

Overall Height:

4.156 inches

Overall Width:

6.656 inches

Mounting Hole Diameter:

0.138 inches

Scale Division Quantity:

60 single indicator 1st range

Furnished Items And Quantity:

Nut 4; washer4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

4.090 inches

Meter Body Width Behind Mounting Flange:

5.700 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

-3.0 to 3.0 volts, dc single indicator 1st range

Scale Selection Method:

Switch

Meter Body Height Behind Mounting Flange:

3.200 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

4 threaded stud

Special Markings:

115 vac; hi; lo; signal input

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0