

View Online at <https://aerobasegroup.com/nsn/6625-00-345-8098>

Circuit Current For Which Designed:

Dc

Overall Length:

2.650 inches

Mounting Hole Diameter:

Between 0.120 inches and 0.130 inches

Scale Division Quantity:

2 single indicator single range

Overall Diameter:

2.695 inches

Environmental Protection:

Shock resistant and vibration resistant and watertight

Mounting Bolt Circle Diameter:

2.440 inches

Furnished Items And Quantity:

Mtg hdw 3; term. Hdw 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

50.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.600 inches

Meter Body Diameter Behind Mounting Flange:

2.210 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Single line at center of scale only

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Features Provided:

Knife edge pointer and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Special Features:

Ruggedized

Special Markings:

Null indicator beneath scale

Material:

Stainless steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel semigloss

Style Designator:

Round flush mtg

Supplementary Features:

Internal resistance: 1500 ohms plus or minus 20 percent

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0