NSN 6625-00-351-5958

Signal Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-351-5958

| Mounting Type: |
|-------------------------------------|
| Rack |
| Overall Length: |
| 13.500 inches |
| Overall Height: |
| 13.625 inches |
| Overall Width: |
| 17.000 inches |
| Current Type: |
| Ac |
| Frequency Rating: |
| Between 50.0 hertz and 100.0 hertz |
| Case Material: |
| Aluminum |
| Case Surface Treatment: |
| Enameled |
| Frequency Range Rating: |
| +0.800/+2100.000 megahertz |
| Accessory Component Quantity: |
| 1 |
| Accessory Controlling Agency: |
| Hewlett-packard co |
| Accessory Identifying Number: |
| Ac-16f type no. |
| Internal Battery Accommodation: |
| Not included |
| Output Impedance Rating: |
| 50.0 ohms |
| Voltage Rating: |
| Between 110.0 volts and 230.0 volts |
| Frequency Band Quantity: |
| 1 |
| Modulation Type: |
| Pulse |
| Accessory Component Name: |
| Rf cable assembly |
| Calibration Accuracy Rating: |
| Porm 1 percent |
| Crystal Controlled Feature: |
| Not provided |
| Calibrated Signal Output Range: |
| 0.4 0.000 |

0.1 uv to 0.223 v

NSN 6625-00-351-5958

Signal Generator - Page 2 of 2



| Signal Output Constancy: |
|---------------------------------------------------|
| Porm 1 db maximum variation throughout freq range |
| Modulator Location: |
| Internal |
| Pulse Repetition Frequency Rating: |
| 60.0 hertz |
| Modulation Degree: |
| 5.0 deviation |
| Phase: |
| Single |
| Functional Classification: |
| Bb-1.1 |
| Entry Date: |
| 90-10-25 |
| Type/model Designation: |
| An/urm-49a |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiia: |

T320-j