

View Online at <https://aerobasegroup.com/nsn/6625-00-352-0028>

Overall Length:

15.250 inches

Overall Height:

15.000 inches

Overall Width:

17.125 inches

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 1000.0 hertz

Voltage Rating:

Between 100.0 volts and 130.0 volts

Beam Quantity:

1

Mounting Method:

Table

Screen Size:

3 in.

Sweep Circuits:

Included

Generator Driven Feature:

Not included

Sweep Circuit Type:

Vertical and horizontal

Sweep Frequency Range:

+8.000/+800000.000 hertz

Trigger Sweep Voltage Amplitude Rating:

Between 25.0 volts and 50.0 volts

Trigger Sweep Polarity Switch:

Included

Trigger Sweep Marker Intervals:

0.2, 1.0, 10, 100, and 500 usec

Expanded Sweep:

Not provided

Amplifier Deflection Sensitivity Provision:

Provided

Vertical Deflection Sensitivity Voltage Rating:

50.0 millivolts rms per inch

Horizontal Deflection Sensitivity Voltage Rating:

3.5 volts any acceptable outside diameter

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Provided

Direct Connection Vertical Deflection Sensitivity Voltage Rating:

110.0 volts any acceptable outside diameter

Direct Connection Horizontal Deflection Sensitivity Voltage Rating:

150.0 volts rms per inch

Frequency Response Rating:

Provided

X-axis Frequency Response Rating:

Between 8.0 hertz and 800000.0 hertz

Y-axis Frequency Response Rating:

Between 2.0 hertz and 8000000.0 hertz

Z-axis Frequency Response Rating:

Between 6.0 hertz and 5000000.0 hertz

Amplifier Input Impedance Rating Provision:

Not provided

Calibrated Screen Scale:

Not included

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Not provided

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

T320-g