NSN 6625-00-352-0028

Oscilloscope - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-352-0028
Overall Length:
15.250 inches
Overall Height:
15.000 inches
Overall Width:
17.125 inches
Current Type:
Ac
Frequency Rating:
Between 50.0 hertz and 1000.0 hertz
Voltage Rating:
Between 100.0 volts and 130.0 volts
Beam Quantity:
1
Mounting Method:
Table
Screen Size:
3 in.
Sweep Circuits:
Included
Generator Driven Feature:
Not included
Sweep Circuit Type:
Vertical and horizontal
Sweep Frequency Range:
+8.000/+800000.000 hertz
Trigger Sweep Voltage Amplitude Rating:
Between 25.0 volts and 50.0 volts
Trigger Sweep Polarity Switch:
Included
Trigger Sweep Marker Intervals:
0.2, 1.0, 10, 100, and 500 usec
Expanded Sweep:
Not provided
Amplifier Deflection Sensitivity Provision:
Provided
Ventical Deflection Constitute Veltons Bathan

Vertical Deflection Sensitivity Voltage Rating:

50.0 millivolts rms per inch

Horizontal Deflection Sensitivity Voltage Rating:

3.5 volts any acceptable outside diameter

Input Intensity Modulation Feature:

Not provided

NSN 6625-00-352-0028

Oscilloscope - Page 2 of 2



Plate Direct Connection Deflection Sensitivity Provision:
Provided
Direct Connection Vertical Deflection Sensitivity Voltage Rating:
110.0 volts any acceptable outside diameter
Direct Connection Horizontal Deflection Sensitivity Voltage Rating:
150.0 volts rms per inch
Frequency Response Rating:
Provided
X-axis Frequency Response Rating:
Between 8.0 hertz and 800000.0 hertz
Y-axis Frequency Response Rating:
Between 2.0 hertz and 8000000.0 hertz
Z-axis Frequency Response Rating:
Between 6.0 hertz and 5000000.0 hertz
Amplifier Input Impedance Rating Provision:
Not provided
Calibrated Screen Scale:
Not included
Trace Storage Tube:
Not included
Camera Recording Device Accommodation:
Not provided
Phase:
Single
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T320-g