

View Online at <https://aerobasegroup.com/nsn/6625-00-389-7399>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

9.875 inches

Overall Height:

6.875 inches

Overall Width:

7.750 inches

Scale Division Quantity:

50 single indicator 3rd range

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Foot pad 4; tilting bail 1; power cord 1; strap 1

Indicator Type:

Dial w/pointer

Installation Design:

Bench

Sensitivity Rating:

300.0 volts

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-1.0 to 1.0 at full scale single indicator all ranges

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Scale Graduation Type:

Nonlinear single indicator 1st range

Measurement Range:

+0.0 to 3.0 decibels single indicator 1st range

Scale Selection Method:

Switch

Features Provided:

External shunting and mirror scale and portable

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

3 receptacle, coaxial

Special Features:

Ruggedized

Special Markings:

Around mode, batt chg; null meter; off; around range switch, 1 v -10; 3 v 0; 10 v +10; 30 v +20; 100 v +30; 300 v +40; 1 mv -70; 3 mv -60; 10 mv -50; 30 mv -40; 100 mv -30; 300 mv -20; rc time constant

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Rectangular or square

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0