Quartz Crystal Unit Test Set - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/6625-00-392-7001

7.000 inchesLength:19.000 inchesAc Voltage Rating:Between 110.0 volts and 120.0 voltsFrequency Rating:Between 50.0 hertz and 1720.0 hertzInternal Battery Accommodation:Not includedMaterial And Location:Aluminum carrying caseTest Type For Which Designed:Measurement of crystal frequency; measurement of crystal activityOperating Test Capability:Single generator range 200 to 1200 kcPhase:SingleHeight:9.000 inchesFsc Application Data:Type no.An/tsm-2Shelf Life:N/aUnit Of Measure:-Demilitarization:NoFig:T228-a	Width:	
19.000 inches Ac Voltage Rating: Between 110.0 volts and 120.0 volts Frequency Rating: Between 50.0 hertz and 1720.0 hertz Internal Battery Accommodation: Not included Material And Location: Aluminum carrying case Test Type For Which Designed: Measurement of crystal frequency; measurement of crystal activity Operating Test Capability: Single generator range 200 to 1200 kc Phase: Single Height: 9.000 inches Fsc Application Data: Type no.An/tsm-2 Shelf Life: N/a Unit Of Measure: Demilitarization: No	7.000 inches	
Ac Voltage Rating: Between 110.0 volts and 120.0 volts Frequency Rating: Between 50.0 hertz and 1720.0 hertz Internal Battery Accommodation: Not included Material And Location: Aluminum carrying case Test Type For Which Designed: Measurement of crystal frequency; measurement of crystal activity Operating Test Capability: Single generator range 200 to 1200 kc Phase: Single Height: 9.000 inches Fsc Application Data: Type no.An/tsm-2 Shelf Life: N/a Unit Of Measure: Demilitarization: No	Length:	
Between 110.0 volts and 120.0 volts Frequency Rating: Between 50.0 hertz and 1720.0 hertz Internal Battery Accommodation: Not included Material And Location: Aluminum carrying case Test Type For Which Designed: Measurement of crystal frequency; measurement of crystal activity Operating Test Capability: Single generator range 200 to 1200 kc Phase: Single Height: 9.000 inches Fsc Application Data: Type no.An/tsm-2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	19.000 inches	
Frequency Rating: Between 50.0 hertz and 1720.0 hertz Internal Battery Accommodation: Not included Material And Location: Aluminum carrying case Test Type For Which Designed: Measurement of crystal frequency; measurement of crystal activity Operating Test Capability: Single generator range 200 to 1200 kc Phase: Single Height: 9.000 inches Fsc Application Data: Type no.An/tsm-2 Shelf Life: N/a Unit Of Measure: Demilitarization: No	Ac Voltage Rating:	
Between 50.0 hertz and 1720.0 hertz Internal Battery Accommodation: Not included Material And Location: Aluminum carrying case Test Type For Which Designed: Measurement of crystal frequency; measurement of crystal activity Operating Test Capability: Single generator range 200 to 1200 kc Phase: Single Height: 9.000 inches Fsc Application Data: Type no.An/tsm-2 Shelf Life: N/a Unit Of Measure: Demilitarization: No	Between 110.0 volts and 120.0 volts	
Internal Battery Accommodation: Not included Material And Location: Aluminum carrying case Test Type For Which Designed: Measurement of crystal frequency; measurement of crystal activity Operating Test Capability: Single generator range 200 to 1200 kc Phase: Single Height: 9.000 inches Fsc Application Data: Type no.An/tsm-2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Frequency Rating:	
Not included Material And Location: Aluminum carrying case Test Type For Which Designed: Measurement of crystal frequency; measurement of crystal activity Operating Test Capability: Single generator range 200 to 1200 kc Phase: Single Height: 9.000 inches Fsc Application Data: Type no.An/tsm-2 Shelf Life: N/a Unit Of Measure: Demilitarization: No	Between 50.0 hertz and 1720.0 hertz	
Material And Location: Aluminum carrying case Test Type For Which Designed: Measurement of crystal frequency; measurement of crystal activity Operating Test Capability: Single generator range 200 to 1200 kc Phase: Single Height: 9.000 inches Fsc Application Data: Type no.An/tsm-2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Internal Battery Accommodation:	
Aluminum carrying case Test Type For Which Designed: Measurement of crystal frequency; measurement of crystal activity Operating Test Capability: Single generator range 200 to 1200 kc Phase: Single Height: 9.000 inches Fsc Application Data: Type no.An/tsm-2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not included	
Test Type For Which Designed:Measurement of crystal frequency; measurement of crystal activityOperating Test Capability:Single generator range 200 to 1200 kcPhase:SingleHeight:9.000 inchesFsc Application Data:Type no.An/tsm-2Shelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Material And Location:	
Measurement of crystal frequency; measurement of crystal activity Operating Test Capability: Single generator range 200 to 1200 kc Phase: Single Height: 9.000 inches Fsc Application Data: Type no.An/tsm-2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Aluminum carrying case	
Operating Test Capability: Single generator range 200 to 1200 kc Phase: Single Height: 9.000 inches Fsc Application Data: Type no.An/tsm-2 Shelf Life: N/a Unit Of Measure: Demilitarization: No	Test Type For Which Designed:	
Single generator range 200 to 1200 kc Phase: Single Height: 9.000 inches Fsc Application Data: Type no.An/tsm-2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Measurement of crystal frequency; measureme	ent of crystal activity
Phase: Single Height: 9.000 inches Fsc Application Data: Type no.An/tsm-2 Shelf Life: N/a Unit Of Measure: Demilitarization: No	Operating Test Capability:	
Single Height: 9.000 inches Fsc Application Data: Type no.An/tsm-2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Single generator range 200 to 1200 kc	
Height: 9.000 inches Fsc Application Data: Type no.An/tsm-2 Shelf Life: N/a Unit Of Measure: Demilitarization: No	Phase:	
9.000 inches Fsc Application Data: Type no.An/tsm-2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Single	
Fsc Application Data: Type no.An/tsm-2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Height:	
Type no.An/tsm-2 Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	9.000 inches	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Fsc Application Data:	
N/a Unit Of Measure: Demilitarization: No Fiig:	Type no.An/tsm-2	
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:	
 Demilitarization: No Fiig:	N/a	
No Fiig:	Unit Of Measure:	
No Fiig:		
Fiig:	Demilitarization:	
-	No	
T228-a	Fiig:	
	T228-a	