

View Online at <https://aerobasegroup.com/nsn/6625-00-400-8212>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

1.630 inches

Overall Height:

1.786 inches

Overall Width:

1.778 inches

Scale Division Quantity:

1 single indicator single range

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Nut 4; lockwasher 2; shunt wire 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

5.0 microamperes

Dial Scale Marking Color:

Green single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.250 inches

Meter Body Diameter Behind Mounting Flange:

1.497 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Input set; green zone at center scale

Mounting Facility Type And Quantity:

1 ring and 1 threaded body

Scale Graduation Type:

Linear single indicator single range

Features Provided:

External shunting and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Special Markings:

On back, sealed do not open

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0