NSN 6625-00-400-8226

Ammeter - Page 1 of 2



| view Online at https://aerobasegroup.com/hsn/oo25-00-400-o226 |
|---|
| Circuit Current For Which Designed: |
| Dc |
| Dielectric Withstanding Voltage In Volts: |
| 5000.0 |
| Overall Length: |
| 1.219 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.344 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.344 inches |
| Overall Height: |
| 1.722 inches |
| Overall Width: |
| 1.722 inches |
| Mounting Hole Diameter: |
| 0.375 inches |
| Scale Division Quantity: |
| 10 single indicator single range |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.000 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 1.484 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |

Scale Graduation Type:

Linear single indicator single range

NSN 6625-00-400-8226

Ammeter - Page 2 of 2

A310a0



| Measurement Range: |
|--|
| +0.0/+1.0 milliamperes, dc single indicator single range |
| Features Provided: |
| Zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 turret |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Rectangular flush mtg |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiia: |