

View Online at <https://aerobasegroup.com/nsn/6625-00-404-3277>

Circuit Current For Which Designed:

Dc

Overall Length:

1.172 inches

Mounting Stud Length:

0.250 inches

Overall Diameter:

2.250 inches

Environmental Protection:

Shock resistant and vibration resistant

Distance Between Mounting Facility Centers:

1.500 inches

Furnished Items And Quantity:

Nut 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

50.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-5.0/+5.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.813 inches

Meter Body Diameter Behind Mounting Flange:

2.000 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 clamp and 2 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

-200.0/+200.0 milliamperes, dc single indicator single range

Mounting Stud Diameter:

0.138 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Special Features:

Ruggedized; solvent resistant

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0