

View Online at <https://aerobasegroup.com/nsn/6625-00-404-3277>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

1.172 inches

**Mounting Stud Length:**

0.250 inches

**Overall Diameter:**

2.250 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Distance Between Mounting Facility Centers:**

1.500 inches

**Furnished Items And Quantity:**

Nut 4

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Two hole/stud

**Sensitivity Rating:**

50.0 millivolts

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-5.0/+5.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

0.813 inches

**Meter Body Diameter Behind Mounting Flange:**

2.000 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

1 clamp and 2 threaded stud

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

-200.0/+200.0 milliamperes, dc single indicator single range

**Mounting Stud Diameter:**

0.138 inches

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder lug and 2 threaded stud

**Special Features:**

Ruggedized; solvent resistant

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, electronic equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0