## NSN 6625-00-404-6912

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-404-6912

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
1500.0
Overall Length:
1.578 inches
Overall Height:  1.750 inches
Overall Width:
1.750 inches
Scale Division Quantity:
20 single indicator single range  Environmental Protection:
Environmental Protection:  Airtight and dust registent and fungue registent and heat registent and humidity registent and sheek registent and vibration registent and
Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
water resistant
Furnished Items And Quantity:
Nut 4; lockwasher 2; seal 1
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Sensitivity Rating:
10.0 volts
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0 to 2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
1.625 inches
Meter Body Diameter Behind Mounting Flange:
1.406 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:
1 ring and 1 threaded body

Linear single indicator single range

**Scale Graduation Type:** 

## **NSN 6625-00-404-6912** Voltmeter - Page 2 of 2



Measurement Range:
+0.0 to 10.0 volts, dc single indicator single range
Scale Selection Method:
Terminal
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Features:
Ruggedized
Special Markings:
On back, sealed do not open
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint
Special Test Features:
Complies with mil-m-10304
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0