## NSN 6625-00-405-4383



Null Meter - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/6625-00-405-4383
Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.440 inches
Mounting Hole Diameter:
0.125 inches
Scale Division Quantity:
20 single indicator single range
Overall Diameter:
2.695 inches
Environmental Protection:
Shock resistant and vibration resistant
Mounting Bolt Circle Diameter:
2.440 inches
Furnished Items And Quantity:
Nut 3; washer 3
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
30.0 microamperes
Dial Scale Marking Color:
White single indicator single range
Accuracy In Percent:
-3.0 to 3.0 at full scale single indicator single range
Unable To Decode:

### Unable to decode or unable to decode **Meter Depth Behind Mounting Flange:**

1.170 inches

#### **Meter Body Diameter Behind Mounting Flange:**

2.150 inches

#### **Movement Type:**

Moving coil, permanent magnet

#### **Background Color:**

Black single indicator single range

#### **Pointer Color:**

White single indicator single range

# NSN 6625-00-405-4383

Null Meter - Page 2 of 2



Scale Marking:
10; 5; 0; 5; 10
Mounting Facility Type And Quantity:
3 screw and 3 unthreaded hole
Scale Graduation Type:
Linear single indicator single range
Features Provided:
Magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 screw and 2 solder lug
Special Features:
Ruggedized
Special Markings:
Plus sign under positive terminal; sealed do not open on back of meter
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel
Style Designator:
Round flush mtg
Supplementary Features:
Calibrated 15 degrees from vert, tilted back
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0