

View Online at <https://aerobasegroup.com/nsn/6625-00-406-3554>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.650 inches

Mounting Stud Length:

Between 0.375 inches and 0.625 inches

Overall Diameter:

2.695 inches

Mounting Bolt Circle Diameter:

2.440 inches

Furnished Items And Quantity:

Nuts 4, washers 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

100.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.600 inches

Meter Body Diameter Behind Mounting Flange:

2.210 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

-12.0 to 4.0 decibels single indicator single range

Mounting Stud Diameter:

0.125 inches

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Off, hk, lo, med and hi

Material:

Plastic and steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Cadmium

Style Designator:

Round semi-flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0